
FIRE SUPPRESSION SYSTEM

ILP Based fire suppression for DG container

FIRE SUPPRESSION SYSTEM — ILP with solenoid & LHS TECHNOLOGY AND ITS USES

An ILP-based fire suppression system for a DG genset refers to a system that uses Indirect Low Pressure (ILP) technology, typically associated with clean agent or CO₂ systems. These systems are designed to automatically detect, suppress, and isolate fires in diesel generator compartments, control panels, or rooms, with minimal human intervention.

Let me walk you through the concept and components of an ILP-based fire suppression system tailored for your Diesel Generator setup.



What is an ILP (Indirect Low Pressure) Fire Suppression System?

ILP (Indirect Low Pressure) is a **pre-engineered system** where:

The detection is **pneumatic** (via a heat-sensitive detection tube).

The suppression is done **indirectly** via **nozzles** connected to a suppression agent cylinder.

The system activates **automatically** when heat causes the detection tube to rupture.

This differs from **DLP** (**Direct Low Pressure**), where the detection tube also acts as the discharge nozzle.

ILP-Based System for 2x40 kVA DG Genset

Suitable For:

Generator engine compartments

Enclosed generator rooms

DG control panels

Typical Fire Hazards:

Diesel fuel leaks

Engine oil

Electrical wiring and panels

Hot surfaces and exhausts

System Components (ILP)

Component Description

LHS Cable

UL approved LHS Cable that detects

high heat/fire

Agent Cylinder

Stores suppression agent (Novec

1230, FM-200, CO₂, etc.)

Discharge Nozzles Sprays agent when the system

activates

Control Panel (optional)

Supervises and interfaces with

alarms and DG shut-off

Manual Release Manual override for safety

personnel

Pressure Switch Monitors pressure loss, triggers

alarm or shutdown

DG Shutdown Relay

Turns off generator to cut fuel

source during a fire

Suppression Agents Typically Used in ILP

Agent	Features	Best For
Novec 1230	Clean, safe, no residue, non-toxic	Electronics and enclosed DG rooms
FM-200	Fast, clean, non-conductive	Small to mid-size engine compartments
CO ₂	Cost-effective, non-damaging, oxygen displacement	Unmanned spaces, enclosed gensets
Dry Chemical (ABC)	Powder-based, low cost	Rarely used in ILP for gensets

Installation Layout (Typical for Each DG Set)

LHS Cable routed around the DG engine and control area **Cylinder** mounted externally near the genset **Nozzles** directed toward:

Engine
Fuel filter
Exhaust manifold
Control panel

System triggers when LHS Cable Shots (~175°C/347°F) Agent is released from cylinder through piping to nozzles Optional: Alarm triggers, and generator shuts down

Compliance and Certifications

- •IS 16018, NFPA 2001, or local fire codes
- •CE, UL, or LPCB certified components
- •Follow guidelines for:
- Ventilation safety
- Diesel storage
- Emergency shutoffs

Key Advantages of ILP for DG Sets

- Automatic 24/7 protection
- No power required for detection
- ✓ Quick suppression and isolation
- Compact and modular
- Minimal maintenance compared to traditional systems

FIRE ENGINEERING TECHNOLOGY

ANIL MISHRA| 971365130 | <u>ANIL@FIREENGINEERINGTECHNOLOGY.COM</u> RAHUL SINGH| 9990360705 | <u>RAHUL@FIREENGINEERINGTECHNOLOGY.COM</u>

HTTPS://WWW.FIREENGINEERINGTECHNOLOGY.COM

Regt. Address: H N 227 -228/9, Prashant Enclave, Baprola, Najafgarh, New Delhi-110043

Correspondence Address: Plot No. 71, Sewak Park, Dwarka More Metro Station, Near Pillar No. 776, Uttam Nagar, New Delhi-110059, Delhi, India

Manufacturing Unit 1: PLOT NO - 4 LAXMI VIHAR, PART-3 NAJAFGARHNEW DELHI - 110043

Manufacturing Unit 2: Plot No. 1, Nangali Sakarawati, Najafgarh-110043

Branch Office (Varanasi, Uttar Pradesh): B 35/24, Sarayanandan, Khojwan, Varanasi-221010

Branch Office (Shakti Nagar, Uttar Pradesh): Cinema Road, Anpara, Auri More, Sonbhadra-231225, Uttar Pradesh, India

Branch Office (Gujrat): C/302, Sunrise residency, Chanod Gam, near gram Panchayat Vapi, Valsad, Gujarat 396195